



DATA SHEET

Lightspeed. Solid. Impressive.

Nytro XF1440 NVMe SSD



The Seagate[®] Nytro[®] XF1440 NVMe SSD is designed with optimised power and performance to deliver 5x the bandwidth of SATA SSDs to eliminate performance bottlenecks and significantly improve quality of service in data centres.



Key Features and Benefits

- PCIe Gen3 x4 interface with NVMe protocol
- Best-in-class performance per Watt of up to 30,000 IOPS/W
- Host-selectable power optimisation
- Industry-leading storage density of up to 1.92 TB in a 2.5-inch x 7 mm form factor

Best-Fit Applications

- Public and private cloud
- Hyperscale data centres
- Caching and tiering



Increase Storage Density in Data Centres

The Nytro XF1440 is low-power, high-performance enterprise NVMe SSD in compact form factors engineered to increase storage density, as well as reduce storage footprints and power use in data centres. The Nytro XF1440 SSD enables more computing with less space, energy and cost by delivering the highest performance in the smallest power envelope.

Improve Data Centre Efficiency and Lower TCO

The Nytro XF1440 is a cost-effective, energy-efficient storage solution that combines a high level of serviceability, improved power and cooling efficiency, scalability and space optimisation to help reduce total cost of ownership (TCO) in data centres. The Nytro XF1440 with the SFF-8639 connector enables effortless serviceability and maintenance without any downtime requirements, and features hot-swap capability for easy addition, removal or replacement of SSDs.

Enhanced Enterprise Reliability, Data Protection and Security

By leveraging Seagate's existing enterprise expertise and manufacturing excellence, the Nytro XF1440 SSD delivers the highest levels of data integrity, data security and endurance for critical business applications. The Nytro XF1440 includes features for end-to-end data protection support, LDPC error correction and Seagate RAISE technology for solid reliability and endurance.

With power-loss data protection, the XF1440 helps maintain data integrity to prevent loss of data in the event of unexpected power interruptions. Seagate Secure[™] Self-Encrypting Drive (SED) models¹ support TCG protocol and help companies keep valuable data secure.

¹ Self-Encrypting Drives (SED) are not available in all models or countries. May require TCG-compliant host or controller support.



Specifications	Endurance Optimised for Mixed Workloads		
Capacity	1.6TB	800GB	400GB
Standard Model ¹	ST1600KN0001	ST800KN0001	ST400KN0001
Seagate Secure™ SED Model ^{1,2}	ST1600KN0011	ST800KN0011	ST400KN0011
Features			
Interface	PCIe Gen3 x4 (NVMe)	PCIe Gen3 x4 (NVMe)	PCIe Gen3 x4 (NVMe)
NAND Flash Type	eMLC	eMLC	eMLC
Form Factor	2.5 in x 7 mm	2.5 in x 7 mm	2.5 in x 7 mm
Performance			
Sequential Read (MB/s) Sustained, 128 KB ³	2,500	2,500	2,400
Sequential Write (MB/s) Sustained, 128 KB ³	900	900	500
Random Read (IOPS) Sustained, 4 KB QD64 ³	240,000	240,000	220,000
Random Write (IOPS) Sustained, 4 KB QD64 ³	40,000	33,000	25,000
Random 70R/30W (IOPS) Sustained, 4KB QD64 ³	100,000	80,000	55,000
Endurance/Reliability			
Lifetime Endurance (Drive Writes per Day)	3	3	3
Non-recoverable Read Errors per Bits Read	1 per 10E16	1 per 10E16	1 per 10E16
Mean Time Between Failures (MTBF, hours)	2,000,000	2,000,000	2,000,000
Warranty, Limited (years)	5	5	5
Power Management			
+12 V Max Power (W)	12.5	12.5	12.5
Average Read/Write Power (W)	9	9	9
Average Idling Power (W)	2.5	2.5	2.5
Physical			
Depth (in/mm, max) ⁴	3.951 in/100.35 mm	3.951 in/100.35 mm	3.951 in/100.35 mm
Width (in/mm, max) ⁴	2.75 in/69.85 mm	2.75 in/69.85 mm	2.75 in/69.85 mm
Height (in/mm, max) ⁴	0.276 in/7 mm	0.276 in/7 mm	0.276 in/7 mm
Weight (lb/g)	90 g/0.198 lb	90 g/0.198 lb	90 g/0.198 lb
Carton Unit Quantity	10	10	10
Cartons per Pallet / Cartons per Layer	40/5	40/5	40/5

1 Not all capacities and features may be available in all regions and countries.

2 Not all drives may be available in all countries. Seagate Secure drives meet ISO/IEC 27040 and NIST 800-88 standards and may require use of TCG-compliant host or controller support.

3 Performance data is based on testing under certain workload conditions and is subject to change. 400 GB and 480 GB capacities are limited to 32x 128 Gb die active.

4 These base deck dimensions conform to the Small Form Factor Standard (SFF-8201) found at www.sffcommittee.org. For connector-related dimensions, see SFF-8639.



Specifications	Capacity Optimised for Read-Intensive Workloads		
Capacity	1.92TB	960GB	480GB
Standard Model ¹	ST1920KN0001	ST960KN0001	ST480KN0001
Seagate Secure™ SED Model ^{1,2}	ST1920KN0011	ST960KN0011	ST480KN0011
Features			
Interface	PCIe Gen3 x4 (NVMe)	PCIe Gen3 x4 (NVMe)	PCIe Gen3 x4 (NVMe)
NAND Flash Type	eMLC	eMLC	eMLC
Form Factor	2.5 in x 7 mm	2.5 in x 7 mm	2.5 in x 7 mm
Performance			
Sequential Read (MB/s) Sustained, 128 KB ³	2,500	2,500	2,400
Sequential Write (MB/s) Sustained, 128 KB ³	900	900	500
Random Read (IOPS) Sustained, 4 KB QD64 ³	240,000	240,000	220,000
Random Write (IOPS) Sustained, 4 KB QD64 ³	15,000	12,000	10,000
Random 70R/30W (IOPS) Sustained, 4KB QD64 ³	45,000	35,000	25,000
Endurance/Reliability			
Lifetime Endurance (Drive Writes per Day)	0.3	0.3	0.3
Non-recoverable Read Errors per Bits Read	1 per 10E16	1 per 10E16	1 per 10E16
Mean Time Between Failures (MTBF, hours)	2,000,000	2,000,000	2,000,000
Warranty, Limited (years)	5	5	5
Power Management			
+12 V Max Power (W)	12.5	12.5	12.5
Average Read/Write Power (W)	9	9	9
Average Idling Power (W)	2.5	2.5	2.5
Physical			
Depth (in/mm, max) ⁴	3.951 in/100.35 mm	3.951 in/100.35 mm	3.951 in/100.35 mm
Width (in/mm, max) ⁴	2.75 in/69.85 mm	2.75 in/69.85 mm	2.75 in/69.85 mm, 2.76 in/69.85 mm
Height (in/mm, max) ⁴	0.276 in/7 mm	0.276 in/7 mm	0.276 in/7 mm
Weight (lb/g)	90 g/0.198 lb	90 g/0.198 lb	90 g/0.198 lb
Carton Unit Quantity	10	10	10
Cartons per Pallet / Cartons per Layer	40/5	40/5	40/5

1 Not all capacities and features may be available in all regions and countries.

2 Not all drives may be available in all countries. Seagate Secure drives meet ISO/IEC 27040 and NIST 800-88 standards and may require use of TCG-compliant host or controller support.

3 Performance data is based on testing under certain workload conditions and is subject to change. 400 GB and 480 GB capacities are limited to 32x 128 Gb die active.

4 These base deck dimensions conform to the Small Form Factor Standard (SFF-8201) found at www.sffcommittee.org. For connector-related dimensions, see SFF-8639.

seagate.com



AMERICAS Seagate Technology LLC 10200 South De Anza Boulevard, Cupertino, California 95014, United States, 408-658-1000
 ASIA/PACIFIC Seagate Singapore International Headquarters Pte. Ltd. 7000 Ang Mo Kio Avenue 5, Singapore 569877, 65-6485-3888
 EUROPE, MIDDLE EAST AND AFRICA Seagate Technology SAS 16-18, rue du Dôme, 92100 Boulogne-Billancourt, France, 33 1-4186 10 00

© 2017 Seagate Technology LLC. All rights reserved. Seagate, Seagate Technology and the Spiral logo are registered trademarks of Seagate Technology LLC in the United States and/or other countries. Nytro, the Nytro logo, Seagate Secure and the Seagate Secure logo are either trademarks or registered trademarks of Seagate Technology LLC or one of its affiliated companies in the United States and/or other countries. All other trademarks or registered trademarks are the property of their respective owners. When referring to drive capacity, one gigabyte, or GB, equals one billion bytes; and one terabyte, or TB, equals one trillion bytes. Your computer's operating system may use a different standard of measurement and report a lower capacity. In addition, some of the listed capacity is used for formatting and other functions, and thus will not be available for data storage. Actual data rates may vary depending on operating environment and other factors, such as chosen interface and disk capacity. The export or re-export of Seagate hardware or software is regulated by the U.S. Department of Commerce, Bureau of Industry and Security (for more information, visit www.bis.doc.gov), and may be controlled for export, import and use in other countries. Seagate reserves the right to change, without notice, product offerings or specifications. DS1952.1-1709 GB September 2017